


SANYO

Cadnica


Cell Type KR-1700AU Specifications




| | | | |
|---|-----------|---|-------------------------------|
| Nominal Capacity | | 1700mAh | |
| Nominal Voltage | | 1.2V | |
| Charging Current | Standard | 170mA | |
| | Fast | 2600mA | |
| Charging Time | Standard | 14 to 16Hrs. | |
| | Fast | about 1Hr. | |
| Ambient Temperature | Charge | Standard | 0°C to +45°C [+32°F to 113°F] |
| | | Fast | 0°C to +45°C [+32°F to 113°F] |
| | Discharge | -20°C to +60°C [-4°F to 140°F] | |
| | Storage | -30°C to +50°C [-22°F to 122°F] | |
| Internal Impedance (Av.) (at 50% discharge) | | 17.0mΩ (at 1000Hz) | |
| Weight | | 35g/1.23oz | |
| Dimensions(D)×(H) (with tube) | | 17.0 ⁰ _{-0.5} × 49.5 ⁰ _{-1.2} | mm |
| | | 0.67 ⁰ _{-0.02} × 1.95 ⁰ _{-0.05} | inch |

Typical Characteristics


Charge




Discharge (at high rate)




Charge



Discharge (at high rate)



Discharge (at low rate)



Temperature (Charge & Discharge)

