ELTA | VISIONPRO



Working voltage: 10 - 30V Homologation: ECE R10

IP Rating: IP67

Die-cast Aluminum housing material with PC Lens

Mounting bracket: stainless steel

Color Temperature: 6500 K

EB8004 - 9LED * 3W/27W (square light) with mounting bracket

LED chip: Epistar

Effective lumen: 1400lm

Dimensions: 125mm (h), 108mm (w), 45mm (d)

EB8005 - 9LED * 3W/27W (round light) with mounting bracket

LED chip: Epistar

Effective lumen: 1400lm

Dimensions: 126mm (h), 115mm (w), 50mm (d)

ELTA | VISIONPRO



HALOGEN BEACONS

Working voltage: 12-24V

Homologation: ECE R10 + R65 Dome material: polycarbonate Protection against reverse polarity

Speed limit 110km/h

IP Rating: IP56

-30°C to +50°C extreme temperature reliability

EB8001 – 12/24V, 3-Bolt base

Dimensions: 165mm (h), 141mm (w)

EB8002 – 12/24V, Magnet base

Dimensions: 165mm (h), 141mm (w)

Accessories:

EB8008 - Spare domes for EB8001, EB8002

LED BEACON

40SMD LED

Working voltage: 12-24V

Homologation: ECE R10 + R65 Dome material: polycarbonate Protection against reverse polarity

Speed limit 110km/h IP Rating: IP56

-30°C to +50°C extreme temp. reliability

3 flash patterns

Easy and comfortable flash switching with a push-button integrated into the cigar lighter

EB8003 – 12/24V, Magnet base with push-button cigar lighter, also with option of 3-bolt fixation Dimensions: 95mm (h), 130mm (w)

Accessories:

EB8009 - Extension cable 10m with double switch

BEACONS





ELTA | VISIONPRO



EB8006 - 4LED * 5W/20W Amber

Dimensions: 36mm (h), 110mm (w), 17mm (d)



EB8007 - 6LED * 5W/30W Amber

Dimensions: 36mm (h), 130mm (w), 17mm (d)

LED STROBE LIGHTS

Working voltage: 9 - 30V

IP Rating: IP67

Homologation: ECE R65 + R10

26 Flash patterns

extreme temperature -30°C to +60°C reliability

Light cover: polycarbonate