



NOTES. FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS PER QQ-B-626  
 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 3. PHOSPHOR BRONZE PER QQ-B-750  
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 5. JIS H 3260, C 3501

1. CRIMPED FERRULE  
 HEX CRIMP SIZE .178"  
 2. CRIMPED CONTACT PIN  
 HEX CRIMP SIZE .068"

DIMENSIONS ARE IN MILLIMETERS				PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES				B6121E1-ND3G-5-50	
0.5-6 = ±0.2				APPROVED	DATE
6-30 = ±0.4					10-11-01'
30-120 = ±0.6				CHECKED	DATE
120-315 = ±1					10-11-01'
315-1000 = ±1.6				DRAWN	DATE
1000-2000 = ±2.4					10-11-01'
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

TITLE		<b>Amphenol</b>	
DRAWING NO.		KJ-B6121E1-ND3G-316U-50	
ITEM NO.			

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	FERRULE	NOTE 5	NOTE 2	1	FR-52/44-38/3 X14
5	SLEEVE	DELTRIN	NATURAL	1	SL-25/17X115
4	CONTACT PIN	NOTE 3	NOTE 4	1	B74000-8-25/06
3	INSULATOR	DELTRIN	NATURAL	1	B74050-3-50-B
2	BODY	NOTE 1	NOTE 2	1	B74000-2
1	HOUSING	NOTE 1	NOTE 2	1	B70002-1-38/27