



## Great Compatibility

Apply to 3.6V/3.7V Li-ion/IMR/INR/ICR:  
14500/14650/16340/17335/17500/17670/  
18350/18490/18500/18650/18700/20700/  
21700/22650/25500/26650

1.2V Ni-MH/Ni-CD:  
AAAA/AAA/AA/A/SC/C

Note: Cannot charge protected 20700/21700 batteries

# Innovative LCD Screen Display

Shows All Information You Want (battery power percentage, battery voltage, charge current, battery charged capacity)

By knowing the charging capacity, you can know the real status of your batteries





## Quick Charge Time

Fully charges a 18650 2500mAh battery in 1.5hrs with real 2A charge current

※The data is tested in laboratory environment, only for reference. Actual charging time may differ from the status of the battery and the using environment

## Two Input Ports, Charge Anytime and Anywhere

You can use the power cord to power the charger via AC input port when you are indoors; when you are outdoors or on journey, you can use the Micro USB port. Shares one adapter with your phone, cost-effective and eco-friendly





## 0V Activation Function

Most batteries we discarded are over-discharged batteries, and 0V Activation Function brings them back to life. Originally invented by Shenzhen XTAR Electronics Co., Ltd, this technology has been followed-up by other companies. We are extremely honored to improve the overall level of the industry



# TC-CC-CV Three-Stage Charging

This charger regulates the voltage and current delivered to the batteries in three automatic stages, to ensure batteries receive optimum charging with minimal wear and tear





## Soft Start

When start charging the batteries, this charger will increase the output current slowly to protect the batteries

# 6 Protections, 3 Certificates, 2 Insurances

**RoHS** **FC** **CE**



Reverse polarity  
protection



Short circuit  
protection



Temperature  
monitoring



CPIC Product  
Insurance



Flame retardant  
material



1 year  
warranty



Over-discharge  
protection



Over heat  
protection



Over-charge  
protection



# X2 Specifications

Model	X2
Input	100-240V~ 50/60Hz 0.4A DC 5V 2.1A
Constant Current	2Ax1/1Ax2/0.5Ax2
Cut-Off Voltage	4.20 ± 0.05V/ 1.45±0.1V
Net Weight	125g
Size	L135*W75*H38mm
Operating Temperature	0-40°C

# Packing

X2, USB power cord, instruction manual

