

# HITPOINT

TEL:8862-26013311

FAX:8862-26013898

NO.4 Lane 505, Zhongzheng Rd., Linkou Shiang, Taipei, Taiwan 24445 . R.O.C

## Piezo Siren PS-733EWDRQ

(ROHS)

DATE:2017.07.19


### 1 . Electrical Characteristics

VER .:1

Resonant Frequency (KHz)	2.5 ~ 4.5
Operating Voltage (Vdc)	5 ~ 15
Rated Voltage (Vdc)	12
Current Consumption (mA/max.)	200 at Rated Voltage
Sound Pressure Level (dB/min.)	85 at 300cm at Rated Voltage
Tone/Pulse Rate (Hz)	Sweep
Operating Temperature (°C)	-20 ~ +70
Storage Temperature (°C)	-30 ~ +80

### 2 . Dimensions and Material

#### 2-1 Shape




Unit : mm



# HITPOINT

TEL:8862-26013311  
FAX:8862-26013898

NO.4 Lane 505, Zhongzheng Rd., Linkou Shiang, Taipei, Taiwan 24445 . R.O.C



## 2-2 Material

Housing	PC (Color : RED )
Lead Wire	28 AWG
Weight (Gram)	25.2


## 3. TESTING METHOD


### · *Standard Measurement conditions*

Temperature:  $25 \pm 2$  °C Humidity: 45-60%

### · *Acoustic Characteristics*

*The oscillation frequency, current consumption and sound pressure are measured by the measuring instruments shown below.*





# HITPOINT

TEL:8862-26013311

FAX:8862-26013898

NO.4 Lane 505, Zhongzheng Rd., Linkou Shiang, Taipei, Taiwan 24445 . R.O.C

## 4. RELIABILITY

<b>ITEMS</b>	<b>METHOD OF TEST AND MEASUREMENTS</b>	<b>PERFORMANCE</b>
<i>Coldness withstanding</i>	<i>After 98 hours of being exposed to -30℃ environment, should be returned to normal environment for 2 hours, then re-proceed to test.</i>	<i>No abnormality shall exist</i>
<i>Hotness withstanding</i>	<i>After 98 hours of being exposed to +80℃ environment, should be returned to normal environment for 2 hours, then re-proceed to test.</i>	<i>No abnormality shall exist</i>
<i>Humidity withstanding</i>	<i>After 98 hours of being exposed to 40℃ 95%RH environment in actual operation, should be returned to normal environment for 2 hours, then re-proceed to test.</i>	<i>No abnormality shall exist</i>
<i>Durability</i>	<i>10sec on/10sec off ; 1000hours(180000 cycles)</i>	<i>No abnormality shall exist</i>
<i>Vibration withstanding</i>	<i>Linear vibrate frequency rate: 5~55Hz Time:180sec , applied in X, Y and Z directions for 3 times each.</i>	<i>No abnormality shall exist</i>

## 5. PACKAGE METHOD

<1> 36pcs per box , Total 10 boxes per carton , total 360pcs carton;

Volume: L\*W\*H=520\*335\*290mm

<2 >N . W . : ; 9.1 KGS ; G . W . : 11.1KGS ;

< 3 > RoHS Mark: