



PANEL CUTOUT
MAX.PANEL THICKNESS
6 mm

FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人

Contact Composition

Operation Position	Switch Type	90° Two Position	
		1NO1NC	2NO2NC
↻			
↻			

"□"	Contact structure
11	1NO 1NC
22	2NO 2NC

"◇"	Operation position
2	Two Position

"◆"	Operation type
1	Maintain
3	Return

Part Number: LAS1-AF-□X/◇◆/△/▲/◎

"△"	Lamp Color
R	Red
G	Green
Y	Yellow

"▲"	Lamp Voltage
6V	AC/DC 6V
12V	AC/DC 12V
24V	AC/DC 24V
110V	AC/DC 110V
220V	AC/DC 220V
Other voltage can be made to order	

"◎"	IP class
No Letter	IP40
P	IP65

SPECIFICATIONS:

- 1.Switch Rating: AC220V/0.5A, DC110V/0.1A.
- 2.Mechanical Life: ≥200,000cycles.
- 3.Electrical Life: ≥50,000cycles.
- 4.Contact Resistance: ≤50mΩ.
- 5.Insulation Resistance: ≥100MΩ.
- 6.Dielectric Strength:
Between contact and lamp terminals: AC 2,000V, RMS 50Hz, 1min;
Between terminals of the same pole: AC 1,500V, RMS 50Hz, 1min;
Between terminals of different pole: AC 2,000V, RMS 50Hz, 1min.
- 7.Operating Temperature: -25℃~ +55℃(No Freezing).
- 8.IP Class: IP40,IP65(Maintain can made to order).
- 9.Terminal Type: Pin Terminal(2.8 x 0.5mm).

MATERIALS:

- 1.Contact: Silver alloy.
- 2.Head: PC.
- 3.Body: PC.
- 4.Base: PBT.

BRAND 品牌	ONPOW	红波按钮制造有限公司 ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.	
USED 用途	APPD 审核	CH	2020/04/26
FINISH 处理	CHKD 校对	NCH	2020/04/26
SCALE 比例	1.4 : 1	UNIT 单位	mm
DR. 制图	ZPD	2020/04/26	
DIMENSIONS		TOLERANCE	
0.00 TO 18.00mm		±0.43mm	
18.01 TO 30.00mm		±0.52mm	
30.01 TO 50.00mm		±0.62mm	
50.01 TO 80.00mm		±0.74mm	
TITLE 名称	LAS1-A Series selector switch		
DWG NO. 图号	LAS1-AF-X二位置带灯		SIZE 图纸 A4
FILE NAME 档案名称	LAS1-A-X.DWG	SHEET 张	1 / 1
		REV. 更改	1