

## Clevis joints with spring-loaded fixing clip: GERMF and GELMF



- Single piece design
- Easy to assemble
- Easy assembly also in hard to reach locations
- Can be used in combination with series E rod ends
- Corrosion-resistant and lightweight



### Order key

Type	Size	Options
<b>G</b>	<b>E ... M F - 04</b>	
<b>Clevis joint</b>	<b>Dimensional series E</b>	<b>Thread</b>
	<b>Thread</b>	<b>Metric</b>
	<b>Spring-loaded fixing clip</b>	
	<b>Inner-Ø [mm]</b>	

Thread  
L = left-hand thread  
R = right-hand thread



**Material:**  
igumid G ► Page 1235

## Technical data

Part No.		Max. static tensile strength		Max. static radial load		Weight
		Short term	Long term	Short term	Long term	
Right-hand thread	Left-hand thread	[N]	[N]	[N]	[N]	[g]
GERMF-04 M3.5	GELMF-04 M3.5	500	250	250	125	1.3
GERMF-04	GELMF-04	500	250	250	125	1.3
GERMF-05 DIN M4	GELMF-05 DIN M4	800	400	250	125	2.3
GERMF-05 DIN M5	GELMF-05 DIN M5	800	400	250	125	2.3
GERMF-05 DIN M5 LS <sup>22)</sup>	GELMF-05 DIN M5 LS <sup>22)</sup>	800	400	250	125	2.3
GERMF-05	GELMF-05	900	450	250	125	3.8
GERMF-06	GELMF-06	1,300	650	300	150	3.9
GERMF-06 LS <sup>22)</sup>	GELMF-06 LS <sup>22)</sup>	1,300	650	130	65	3.9
GERMF-08	GELMF-08	2,100	1,050	650	325	9.1
GERMF-10	GELMF-10	3,000	1,500	800	400	18.2
GERMF-10 F	GELMF-10 F	3,000	1,500	800	400	18.2
GERMF-12	GELMF-12	3,500	1,750	900	450	28.6
GERMF-12 F	GELMF-12 F	3,500	1,750	900	450	28.6
GERMF-16	GELMF-16	7,000	3,500	1,200	600	61.8
GERMF-16 F	GELMF-16 F	7,000	3,500	1,200	600	61.8

<sup>22)</sup> LS = longer shank



Single components: spring-loaded fixing clip GEFM  
► Page 640