



Type K, Mineral Insulated thermocouple



- Mineral insulated K thermocouples
- Very rugged and flexible
- Stainless steel (310) Sheath
- Particularly suitable for high pressure, high vacuum or high vibration applications
- Max temperature of probe 1100°C (K)
- Plain pot seal (max temp 200°C)
- 7/0.2mm PFA Insulated Lead

About Labfacility

Formed in 1971, Labfacility specialize in the field of Temperature and Process Measurement.

We are the largest UK manufacturer of both temperature sensors and thermocouple connectors

Quality & Service

Quality and Service are key elements in the continued growth of Labfacility.

Technical support is always freely available from our experienced technical sales teams and the company has ISO9001 accreditation.

Contact Details

Email
sales@labfacility.com

Website
www.labfacility.com

Type	Dia (mm)	Probe Length (mm)	Cable Length (mtrs)	Manufacturer Part No	Farnell Order #
K	1	100	2	MA-ISK-S10-100-P1-2.0-C2-T	128-9614
K	1	250	2	MA-ISK-S10-250-P1-2.0-C2-T	128-9617
K	1	500	2	MA-ISK-S10-500-P1-2.0-C2-T	128-9618
K	1	1000	2	MA-ISK-S10-1000-P1-2.0-C2-T	128-9619
K	1.5	100	2	MA-ISK-S15-100-P1-2.0-C2-T	128-9620
K	1.5	150	2	MA-ISK-S15-150-P1-2.0-C2-T	128-9621
K	1.5	250	2	MA-ISK-S15-250-P1-2.0-C2-T	128-9622
K	1.5	500	2	MA-ISK-S15-500-P1-2.0-C2-T	128-9623
K	1.5	1000	2	MA-ISK-S15-1000-P1-2.0-C2-T	128-9624
K	1.5	2000	2	MA-ISK-S15-2000-P1-2.0-C2-T	128-9625
K	3	100	2	MA-ISK-S30-100-P1-2.0-C2-T	128-9626
K	3	250	2	MA-ISK-S30-250-P1-2.0-C2-T	128-9629
K	3	500	2	MA-ISK-S30-500-P1-2.0-C2-T	128-9630
K	3	1000	2	MA-ISK-S30-1000-P1-2.0-C2-T	128-9631
K	3	2000	2	MA-ISK-S30-2000-P1-2.0-C2-T	128-9632
K	6	100	2	MA-ISK-S60-100-P1-2.0-C2-T	128-9633
K	6	150	2	MA-ISK-S60-150-P1-2.0-C2-T	128-9634
K	1	100	1	MA-ISK-S10-100-P1-1.0-C2-T	128-9641
K	1	250	1	MA-ISK-S10-250-P1-1.0-C2-T	128-9642
K	1.5	2000	1	MA-ISK-S15-2000-P1-1.0-C2-T	128-9647
K	3	500	1	MA-ISK-S30-500-P1-1.0-C2-T	128-9648